



## LED 40W LINEAR FLOATING

**VOL-1200FPL-040-NW**



### SECTION 1: SPECIFICATIONS

POWER	40W
VOLTAGE	100-277V
LIGHT OUTPUT	4800 lm
EFFICACY	120 lm/W
RATED FREQUENCY	50Hz / 60Hz
CCT	3000-6000K
POWER FACTOR	0.97
OPERATIONAL TEMPERATURE	-25°-40° C

#### CERTIFICATIONS



## SECTION 2: FEATURES

MODULAR LINEAR LIGHTING LUMINAIRE. FOR INDOOR APPLICATIONS WHERE CONTINUOUS LINEAR LIGHTING IS DESIRED SUCH AS PERIMETER LIGHTING APPLICATIONS. THIS LUMINAIRE IS SUITABLE FOR SURFACE, SUSPENDED OR RECESSED, INDIVIDUALLY OR IN CONTINUOUS ROWS WHILE OFFERING AN OPTIONAL UPLIGHT COMPONENT WITH AN INTERNAL BAFFLE THAT SEPERATES UPLIGHT AND DOWNLIGH COMPONENTS.

LONG LIFE LED<sub>s</sub> COUPLED WITH HIGH EFFICIENCY DRIVERS PROVIDE QUALIFIED ILLUMINATION. RATED TO DELIVER PERFORMANCE >50,000 HOURS. OPTIONAL SUPPLIED WITH DIMMABLE DRIVER (1-10V). STANDARD 4 FT NOMINAL WHITE. AIRCRAFT CABLE FOR SUSPENDED-MOUNT APPLICATION IN OFFICE AREAS, RETAIL STORES, CORRIDORS, CLASSROOMS, LIBRARIES, HOSPITALITY.

WITHOUT SCREWS ON THE END CAPS, QUICKER FITTING FOR CONTINUOUS RUN WITHOUT SHADOW. SUSPENDED, CEILING, RECESSED MOUNTED FOR DIFFERENT APPLICATIONS.

## SECTION 3: DIMENSIONS

### LENGTH

48 (1176)

### WIDTH

2 3/4 (73)

### DEPTH

3 1/7 (80)

