



80W QUATTRO EXPLOSION PROOF EMERGENCY

VOL-EEPL-080-CW



SECTION 1: SPECIFICATIONS

POWER	80W
VOLTAGE	85-227V
RATED FREQUENCY	50Hz/60Hz
LIGHT OUTPUT	8800 lm
CCT	5500-6500K (CW)
POWER FACTOR	0.98
RUN TIME	2.5-3 HRS
BEAM ANGLE	120°
IP RATING	67
OPERATIONAL TEMPERATURE	-40°-55°C
HOUSING MATERIAL	HEAVY DUTY COPPER FREE ADC12 AL ALLOY
WEIGHT	8.1 kg

CERTIFICATIONS



SECTION 2: CERTIFICATIONS MET

THE ANTI-CORROSION, ABRASION PROOF, POWER COATED COVER WHICH IS DUST PROOF & WATER PROOF MAKES THE LAMP AN EXCELLENT OPTION FOR ALL KINDS OF HIGH STRESS ENVIRONMENTS

SHOCK AND VIBRATION RESISTANT TEMPERED GLASS, SUPER CLEAR 95% LIGHT TRANSMIT RATE

SURFACE TREATMENT - POWER PAINTED, SALT RESISTANT

CSA 250, UL1598, CSA 137, UL844
IEC/EN 60079-0, IEC/EN 60079-1
IEC/EN60079-15, IEC/EN60079-31
Class 1 Div 1, Group B,C,D
Class 1 Div 2, Group A,B,C,D
Class II Div 1, Group E,F,G
Class II Div 2, Group E,F,G
Class III, Ex d IIC T6
Ex nA IIC T6,
Ex tb IIIC T6

SECTION 3: MOUNTING OPTIONS

HOOK



ADJUSTABLE WALL MOUNT



WIRELESS U-BRACKET

