



## GRILLE LIGHT 2x2 FT

**VOL-GPL-2x2-CW**

### SECTION 1: SPECIFICATIONS

FITTING COLOUR	WHITE
MATERIAL	IRON BASE + PS DIFFUSER
COLOUR TEMPERATURE	6000-6500K
SUPPLY VOLTAGE	AC85-277V
WATTAGE	48W
DIMMABLE	NO
LUMENS	4600 LM
POWER FACTOR	>0.9
ESTIMATED LIFE SPAN	30,000 HOURS
IP RATING	20
BEAM ANGLE	120°

#### CERTIFICATIONS

**RoHS**  
Compliant

**CE**

**UL**

## SECTION 2: INSTALLATION

1. TURN OFF THE POWER
2. CONNECT THE COMMERCIAL POWER WITH THE INPUT OF THE MATCHED POWER, MAKING SURE NO COPPER IS EXPOSED.
3. CONNECT MATCHED POWER SUPPLY AND PANEL LIGHT TOGETHER THROUGH THE PLUG
4. FIX THE PANEL LIGHT AND POWER SUPPLY AT A SUITABLE PLACE.
5. TURN ON THE POWER

**NOTE: THE PANEL SHOULD BE DRIVEN BY APPOINTED POWER ONLY.**

## SECTION 3: INSTALLATION DETAILS

### APPLICATIONS

HOTEL, MEETING ROOM, OFFICE, HOSPITAL, SCHOOL, AND PLACES WHERE ENERGY SAVING AND HIGH COLOR RENDERING INDEX LIGHTING IS NEEDED

### CONNECTION

COMMERICAL POWER

