

CERTIFICATIONS

ISTED

LINEAR LIGHT 4FT 36W

VOL-LL-036-CW-4FT

SECTION 1: SPECIFICATIONS

POWER	36W	
VOLTAGE	85-277V	
LED	SANAN	
NUMBER OF LEDs	180	
BEAM ANGLE	120°	
MATERIAL	Polycarbonate (PC), Frosted	
LIGHT OUTPUT	4,320lm	
COLOR TEMPERATURE	6000-6500K	
FIXTURE LIFE-SPAN	50,000 HRS	
IP RATING	IP 65	
IMPACT RESISTANCE	IK 10	
OPERATING TEMPERATURE	-20~70°C	
DIMENSIONS	1200 x43 x77mm	

SECTION 2: INSTALLATION

For installation the following materials are required: • 2 pieces of hooks • 2 screws (used to fix the hooks to the wall or ceiling)

- 1 Disconnect the power supply before installation of the light or when conducting any maintenance work.
- 2 Installation and maintenance must be carried out by a qualified personnel or an electrician.
- First connect the waterproof terminal box with L (Brown wire) and N (Blue wire). Always ensure the L and N is 3 matching.
- 4 Insert the lights fitting into the hooks
- Secure the waterproof terminal box properly 5